

FINEO is much more than glass technology: it is pure comfort. This groundbreaking vacuum insulating glass not only delivers amazing energy performance, it also combines exceptional thermal insulation with unprecedented durability.

This thin vacuum insulating glass is elegant and sleek. The Safety range offers protection against personal injury.

FINEO insulates as effectively as triple glazing but is lighter and thinner, meaning it can be installed into existing window frames. This often makes FINEO the most economical solution for renovation and restoration projects.

FINEO is a sustainable investment as it is 100% recyclable. It also has a long life expectancy without loss of performance.



What's so special about it?

What does this mean for you?

SLIM, SLEEK AND AESTHETICAL DESIGN	 An appearance similar as monolithic glass No vacuum evacuation port Suitable for retrofitting(*) into existing windows
OUTSTANDING THERMAL INSULATION	 U-value = 0,7 W/(m².K) For all situations (e.g. sloped or roof glazing)
SAFETY	 Laminated safety glazing Protection against personal injury and fall-through
SUSTAINABLE INVESTMENT	 Designed to perform for several decades
MORE NATURAL DAYLIGHT	Slim design allows in more daylight
HARNESSES MORE FREE SOLAR ENERGY	Lower energy consumptionLower emissions
REDUCES UV RADIATION	Blocks 99% of UV raysReduces discoloration of interior furnishings
EXCEPTIONAL NOISE REDUCTION	Increased soundproofingReduced traffic noise
LEAD-FREE AND RECYCLABLE	100% RecyclableCircular sustainability

(*) retrofitting: replace the existing glass with a FINEO glazing while keeping the original window frame (provided the window frame is in a properly state).





ULTIMATE SLIM DESIGN FOR MAXIMUM INDOOR COMFORT

Light and energy performance (1)

FINITO A	Tot.		EN 410			EN 673
SAFETY by AGC	Thickness [mm]	LT [%]	LR ext [%]	LR int [%]	g [-]	Ug [W/ (m².K)]
FINEO Safety 6	13.9	77	13		0.58	
FINEO Safety 8	14.9	77		14	0.57	
FINEO Safety 10	18.9	76		13 14	0.56	0.7
FINEO Safety 12	20.9	75			0.56	

Acoustic attenuation performance (2)

FINEO by AGC	EN ISO 10140		
	Rw [C;Ctr] [dB]	Rw+Ctr [dB]	
FINEO Safety 8	41 (-2;-4)	37	
FINEO Safety 10	44 (-2;-4) ⁽³⁾	40(3)	
FINEO Safety 12	45 (-2;-5) ⁽³⁾	41 ⁽³⁾	

Production feasibility

•				
DIMENSIONS	Maximum	1.5m x 2.5m or 1.6m x 2.4m		
	Minimum	0.2m x 0.2m		
SHAPE -	Standard	Square or rectangle		
	Shapes	End 2020		

Safety glass tests



- (1) These data are calculated using spectral measurements compliant with standards EN 410 and ISO 9050 (1990). The Uglass-value is calculated according to standard EN 673. Emissivity is measured as per standards EN 673 (Annex A) and EN 12898.
- (2) These sound reduction indexes correspond to a FINEO sample measuring 1,23m x 1,48m as per EN ISO 10140-3. The testing is carried out under laboratory conditions. In-situ performance may vary depending on the actual glazing dimensions, frame system, noise sources, etc.
- (3) Estimated values.
- (1) FINEO sample measuring 0.88m x 1.94m as per EN 12600.



